



FE704HFC WideArea™ Eye/Face Wash, Pedestal Mounted, Hand and Foot Control, Stainless Steel Bowl FE704P-HFC WideArea™ Eye/Face Wash, Pedestal Mounted, Hand and Foot Control, Plastic Bowl

Application: Free standing, pedestal mounted WideArea™ eye/face wash with hand and foot control. Water flow is activated by either flag handle or foot treadle. Four GS-Plus™ spray-type outlet heads deliver a flood of water over a wide area of coverage for complete rinsing of eyes and face.

Spray Head Assembly: Four GS-Plus™ spray heads. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Valve: 1/2" IPS chrome plated brass stay-open ball valve. Valve is US-made with chrome plated brass ball and PTFE seals. Valve is activated by flag handle or foot treadle. Unit remains in operation until handle is returned to closed position.

Bowl: 11-1/8" diameter stainless steel (FE704HFC) or 11-3/4" diameter orange ABS plastic (FE704P-HFC).

Pipe and Fittings: Schedule 40 galvanized steel. Furnished with orange polyethylene pipe covers for high visibility and corrosion resistance.

Supply: 1/2" NPT female inlet. **Waste:** 1-1/4" NPT female outlet.

Sign: ANSI-compliant identification sign.

Quality Assurance: Valve, bowl and spray head assembly is factory assembled and water tested prior to shipment.

Available Options

TM6020 Thermostatic mixing valve precisely blends hot and cold water to deliver tepid water as required by ANSI Z358.1-2014. Refer to "Thermostatic Mixing Valves" section for complete technical and product selection information.
BC Stainless steel bowl cover (FE704HFC only). Cover protects unit against contaminants. Cover is automatically raised when unit is activated.
HS Auxiliary hand-held drench hose for rinsing eyes, face or body.







- FE704HFC WideArea™ Eye/Face Wash, Pedestal Mounted, Hand and Foot Control, Stainless Steel Bowl FE704P-HFC WideArea™ Eye/Face Wash, Pedestal Mounted, Hand and Foot Control, Plastic Bowl
 - Ø11 1/8" (283mm) (4) GS-PLUS™ **SPRAY HEADS** (127mm) POWDER COATED CAST ALUMINUM FLAG HANDLE STAINLESS STEEL BOWL 1/2" NPT FEMALE INLET 1/2" IPS CHROME PLATED 5" **BRASS STAY-OPEN** (127mm) BALL VALVE 4 5/8" (117mm) 29" CHAIN (736mm) 39 1/2" (1003mm) 33 1/2" (851mm) **GALVANIZED STEEL** 1-1/4" NPT PIPE AND FITTINGS **FEMALE OUTLET** STAINLESS STEEL FOOT TREADLE 9 1/4" (235mm) 9 1/4" (102mm) (235mm) DETAIL "A" UNIVERSAL FLOOR FLANGE (229mm) POWDER COATED **CAST ALUMINUM** FLOOR FLANGE (SEE DETAIL "A") EACH GS-PLUS™ SPRAY HEAD HAS A "FLIP-TOP" DUST COVER, INTERNAL Ø7/16" MOUNTING SLOTS FLOW CONTROL AND FILTER TO REMOVE ON 7-5/8" BOLT CIRCLE IMPLIRITIES FROM THE WATER FLOW.

THIS SPACE FOR ARCHITECT/ENGINEER APPROVAL

Due to continuing product improvement, the information contained in this document is subject to change without notice. All dimensions are \pm 1/4" (6mm). rev. 0422 Sign Included

