

- FE775 Eye/Face Wash, Deck Mounted 90° Swivel, Right Hand Mounting
 FE775LH Eye/Face Wash, Deck Mounted 90° Swivel, Left Hand Mounting
 - FE775LH FE775



Application: Eye/face wash for mounting on counter next to sink. Spray heads swivel 90 degrees from storage to operational position. Water flow is activated by flag handle.

Spray Head Assembly: Two FS-Plus[™] spray heads. Each head has a "flip top" dust cover, internal flow control and filter to remove impurities from the water flow.

Valve: 1/2" IPS chrome plated brass stay-open ball valve. Valve is US-made with chrome plated brass ball and PTFE seals.

Mounting: Unit may be mounted on right side (AP775) or left side (AP775LH) of sink. Furnished with locknut and washer for securing unit to countertop. Provide 7/8" diameter hole in counter.

Construction: Polished chrome plated brass.

Supply: 1/2" NPT male inlet.

Sign: ANSI-compliant identification sign.

Quality Assurance: Unit is completely assembled and water

tested prior to shipment.

Available Options

TM6020 Thermostatic mixing valve precisely blends hot and cold water to deliver tepid water as required by ANSI Z358.1-2014. Refer to "Thermostatic Mixing Valves" section for complete technical and product selection information.



- FE775 Eye/Face Wash, Deck Mounted 90° Swivel, Right Hand Mounting
 □ FE775LH Eye/Face Wash, Deck Mounted 90° Swivel, Left Hand Mounting
- STORAGE POSITION FE775LH **FE775** 4 7/8" (76mm) (124mm) 8' (203mm) 12 1/2" (318mm) (2) FS-PLUS™ 6 1/2" (165mm) SPRAY HEADS POWDER COATED CAST ALUMINUM FLAG HANDLE 8 3/8" (213mm) 90° SWIVEL FITTING 4 3/4" (121mm) 1/2" IPS CHROME-PLATED BRASS STAY-OPEN BALL VALVE Ø1 7/8" (48mm) NOTES: EACH FS-PLUS™ SPRAY HEAD HAS A PROVIDE Ø7/8" MOUNTING 2-5/8" "FLIP-TOP" DUST COVER, INTERNAL HOLE IN DECK (22mm) (67mm) FLOW CONTROL AND FILTER TO REMOVE IMPURITIES FROM THE WATER FLOW. 1/2" NPT MALE INLET 2. SECURE UNIT TO COUNTER USING MOUNTING SHANK AND LOCKNUT.

THIS SPACE FOR ARCHITECT/ENGINEER APPROVAL

Due to continuing product improvement, the information contained in this document is subject to change without notice. All dimensions are \pm 1/4" (6mm). rev. 0422

Sign Included

